

Tecnau presents its Thermoplastic Film Tubes Cutter
TC 9010

It is a one web pinless cutter equipped with unwinder and output conveyor.



The **TC 9010** main features include:

- Modular design.
- Microprocessor controlled.
- Oscillating cross blade cartridge with high precision (1/96") and high durability.
- Programmable cut length.
- Speed: up to 13.000 cuts/hr, 12" formats.
- Automatic control of cutting speed and advancing film.
- Film increments of 1/6", 1/8", 1/96".
- Up to 99 cutting program memory.
- Automatic stop at film end.
- Display and keyboard for programming, information, service.



TECHNICAL SPECIFICATIONS **TC 9010**

FILM SPECIFICATIONS:

- specific gravity: 0,92 - 0,96 gr/cc
- thickness: 0,035 - 0,08 mm
- web width: min 22 mm - max 272 mm

SIZE AND WEIGHT:

- length: 1.070 mm
- width: 880 mm
- height: 1.100 mm
- weight: 160 Kg

CUTTER SPEED:

- up to 13.000 12" sheets per hour
- up to 25.000 4" sheets per hour

POWER REQUIREMENTS:

- 230V
- 50 / 60 Hz
- 1,0 KVA



SPEED (cuts per hour)

CARTRIDGE	TC 1010
CUT	Single Cut
Height Form 4"	25.000
Height Form 8"	18.000
Height Form 12"	13.000