



# TC 1550 HS DP2

## Dynamic Punching Unit



### *Dynamic Punching unit for 2-up production*

- ✓ **Four punching wheels for 2-up production**
- ✓ **2, 3 or 4 holes pattern per wheel**
- ✓ **Speed up to 150 m/min for 12" forms**
- ✓ **Read & Punch On The Fly**
- ✓ **On board tensioner/detensioner (optional)**

The TC 1550 HS DP2, dynamic punching unit is the perfect solution to produce reliable documents with accurate punching patterns for easy paper handling and storage.

The TC 1550 HS DP2 has 2 punching devices, with two independent punching wheel on each device for 2-up applications. Wheels can be equipped with 2, 3 or 4 punching patterns to fit different applications.

The TC 1550 HS DP2 performs punching patterns through a OMR, Barcode or Datamatrix reader to ensure on-the-fly application jobs

and maximum flexibility. A vacuum system is integrated into the unit to clean the web and prevent that paper waste is transferred to the following processes.

Tecnau solutions increase productivity, cut labor and paper costs, and even make new applications possible. Global service and around-the-clock support help ensure our reputation as the industry's reliability leader. Innovative products combined with award winning support and service make Tecnau the essential partner for your print operation.




# TC 1550 HS DP2

## Dynamic Punching Unit2

The Dynamic Punching TC 1550 HS DP2 has been developed to work with tight or slack paper webs, in line with Laser Printers, high speed inkjet Digital Printing Systems and finishing equipments. The main feature for this product are:

- ✓ Two punching devices, with two independent punching wheels for 2-up applications.
- ✓ The punch device is activated by 1D or 2D code reading with start/stop motion performing the punch pattern.
- ✓ Different hole diameters available on the same punching wheel (1/4" - 3/8" DIA).
- ✓ Manual adjustment of the vertical file holes line at the paper web position.
- ✓ Programmable punching position.
- ✓ Punching position microprocessor controlled by OMR or Bar Code or D-Matrix readers.
- ✓ "Read & Punch On The Fly" software for automatic detect and perform the applications, switching from one application to another within one sheet module.
- ✓ Up to 89 different applications can be stored.
- ✓ Automatic synchronization after blank paper.
- ✓ Display and keyboard for programming, information and services.
- ✓ Parallel and serial interface.

### Configuration Example



### Technical Specifications

#### Performance / Media

Speed Max	500 ft/min	150 m/min
Feeding	Pinless	
Paper weight	16# bond - 140# index / 60 - 250 gsm	
Web width	6" - 20.5"	152 - 520 mm
Punching Form	6"(*) - 24"	152 - 610 mm
	* for each punching device	
Punching App.	Standard European 2 or 4 holes at 80 mm (Other applications are available on request)	

#### Electrical

Power	400 Vac 3Ph, 50/60 Hz, 8A, 4kW
Air	15 litres/min @ 6 bar pressure

#### Dimensions

Length	52"	1340 mm
Width	42"	1060 mm
Height	48"	1220 mm
Weight	1984 lb	900 kg

### Application Examples



04032017

©2017 Tecna. All rights reserved. The Tecna name and logo are trademarks of Tecna. Tecna reserves the right to make any technical amendments without prior notification.



# TECNAU

w w w . t e c n a u . c o m

Europe	Italy	+39 0125 631678	info.it@tecna.com
	Sweden	+46 372 256 00	info.se@tecna.com
Americas	USA	+1 978 608 0500	info.us@tecna.com
Asia Pacific	China	+86 159 00710147	info.cn@tecna.com
	Singapore	+65 6793 9478	info.sg@tecna.com